

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Standard duty overall dimension of 24" wide x 60" x 69" tall. Four chrome plated wire shelves with one solid stainless base shelf. 5" resilient casters, two with brakes.

Heavy duty overall dimension of 29% wide x 64% long x 72% tall. Chrome-plated dolly base with one solid stainless shelf and four 24% x 60% wire shelves. 6% polyurethane plate casters, two with brake. Enclosure panels on three sides.



Options / Accessories

- □ Cart Cover
- □ Tote boxes
- ☐ Shelf tray
- ☐ Tray slides
- ☐ Undershelf slides

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration	or fabrication	needs,	contact	our	SpecFAB®	Division.
Phone: 302-653-3000 • Fax	: 302-653-2065	• e-ma	il: quotes	@ea	glegrp.com	

Item No.:	
Project No.:	
S.I.S. No.:	

Linen Carts

MODELS:

□ *LC2460C* □ *LCD2460C*

Design and Construction Features—both models

- Carts can be altered to meet changing requirements by adding or removing accessories. Any number of combinations can be made to customize any linen cart for a specific use.
- Numerically calibrated grooved posts, tapered split sleeves and shelf collars combine to make shelving assembly a simple two-step exercise: 1) Snap the split sleeves onto the posts at the desired location, and 2) slide the shelf collars over the split sleeves. A positive lock between the shelf and the split sleeves is created without the use of any tools, becoming stronger as weight is added to the shelving.
- Open-wire construction promotes higher visibility by allowing light to pass through the shelves, permits greater air circulation which helps reduce dust and contamination build-up, and increases the effectiveness of fire-suppression systems.
- Posts are numbered on vertical 1" (25mm) increments to ensure fast and level assembly; shelving can be adjusted up and down every inch for optimum cart configuration.
- All components are chrome-plated.

Standard model

- Four chrome-plated wire shelves.
- One solid stainless steel shelf.
- Chrome-plated 63" (1600mm) posts.
- 5" (127mm) resilient stem casters, two with brake.
- Donut bumpers.

Heavy Duty model

- Four chrome-plated wire shelves.
- · One solid stainless steel shelf.
- Chrome-plated dolly frame with wraparound bumper.
- 6" (152mm) polyurethane casters, two with brake.
- Side and back enclosure panels.
- · Chrome-plated posts.

Certifications / Approvals
NSF

EG05.02 Rev. 06/13



Item No.:	
Project No.:	
S.I.S. No.:	

Linen Carts





Standard Unit

	shelf width odel # in. m		shelf length		ove	erall				
	width				height		weight			
model #	in.	mm	in.	mm	in.	mm	lbs.	kg		
LC2460C	24"	610	60″	1524	69"	1753	190	86.2		

Heavy Duty Unit

, ,	shelf width			shelf length		dolly width		dolly length		overall height		weight	
model #	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg	
LCD2460C	24"	610	60″	1524	29¾"	756	64¾"	1648	72"	1829	240	108.9	

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

Printed in U.S.A. ©2013 by Eagle Group MHC/Retail Display Divisions: Phone 800-637-5100 Rev. 06/13