



Profit from the Eagle Advantage®

Specification Sheet

Item No.:	_____
Project No.:	_____
S.I.S. No.:	_____



ESD cart cover in use

Electronics Accessories

ESD Cart Covers

- Controls electrostatic discharge while protecting contents from moisture and contamination.
- Waterproof, tear-resistant, antibacterial and flame-retardant.
- All covers include flap on one side.
- Covers for “ETC” carts have both side and end flaps for side or end load.
- Comes with paperwork pouch.

Conductive Casters

- Meets Federal Specification #FF-C-88C standards.
- Zinc-plated yolk.
- 5” x 1¼” (127 x 32mm) wheel.
- 200-lb. (90.7 kg) weight capacity.
- Standard 3½” (89mm)-diameter donut bumper.
- Swivel, brake, and rigid casters available.



conductive caster

Aluminum Split Sleeves

- For conductive, over the road or high-temperature installation.
- Set of four.



aluminum split sleeve



plastic conductive split sleeve

Plastic Conductive Split Sleeves

- Set of four.

EAGLE GROUP

100 Industrial Boulevard
Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • 800-441-8440

Fax: 302-653-2065

www.eaglegrp.com • www.eaglemhc.com

For custom configuration or fabrication needs, contact our **SpecFAB® Division**.

Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

EG07.12 Rev. 06/21

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com



Profit from the Eagle Advantage®

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Electronics Accessories



ESD cart cover in use

ESD Cart Covers

model #	fits shelf dimensions		post height		weight	
	in.	mm	in.	mm	lbs.	kg
CZ-63-1836-ESD	18" x 36"	457 x 914	63"	1600	3	1.4
CZ-63-1848-ESD	18" x 48"	457 x 1219	63"	1600	4	1.8
CZ-63-2424-ESD	24" x 24"	610 x 610	63"	1600	3	1.4
CZ-63-2436-ESD	24" x 36"	610 x 914	63"	1600	3	1.4
CZ-63-2448-ESD	24" x 48"	610 x 1219	63"	1600	4	1.8
CZ-63-2460-ESD	24" x 60"	610 x 1524	63"	1600	5	2.3
CZ-49-ETC	31 $\frac{1}{4}$ " x 21 $\frac{1}{2}$ "	807 x 549	49"	1245	3	1.4
CZ-63-ETC	31 $\frac{1}{4}$ " x 21 $\frac{1}{2}$ "	807 x 549	63"	1600	4	1.8

Conductive Casters

zinc model #	type	wheel diameter		wheel face		weight capacity		weight	
		in.	mm	in.	mm	lbs.	kg	lbs.	kg
CSS5-CC	stem/swivel	5"	127	1 $\frac{1}{4}$ "	32	200	90.7	2.5	1.1
CSB5-CC	stem/brake	5"	127	1 $\frac{1}{4}$ "	32	200	90.7	2.8	1.3
CSR5-CC	stem/rigid	5"	127	1 $\frac{1}{4}$ "	32	200	90.7	3.5	1.6

Aluminum Split Sleeves

model #	description
A208908	set of four, with stainless steel rings
A208909	set of four, with zinc rings

Plastic Conductive Split Sleeves

model #	description
A219236	set of four



conductive
caster



aluminum split sleeve



plastic conductive
split sleeve

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC Division: Phone 800-637-5100

Printed in U.S.A.
 ©2021 by Eagle Group

Rev. 06/21

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.