



Profit from the Eagle Advantage®

# Specification Sheet

## Short Form Specifications

Eagle Plate Caster, model \_\_\_\_\_. Resilient or polyurethane tread. Casters with zinc, stainless steel, and polymer boot available. 5" to 8" wheel diameter.

Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_

## Plate Casters

### MODELS:

- CPS\*-\*                       CPR\*P-\*                       PCPS5-250
- CPB\*-\*                       CPL\*Z-\*                       PCPL5-250
- CPR\*-\*                       CPS\*Z-\*                       CPS5S-300
- CPS\*P-\*                       CPR\*Z-\*                       CPB5S-300
- CPB\*P-\*                       CPB\*Z-\*

\* See charts for complete model numbers.



resilient plate caster

### Casters with Resilient Tread

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPS5-200	200	90.7	5"	127	1 1/8"	29	2.8	1.3
brake	CPB5-200	200	90.7	5"	127	1 1/8"	29	2.8	1.3
rigid	CPR5-200	200	90.7	5"	127	1 1/8"	20	2.8	1.3
swivel	CPS5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
brake	CPB5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
rigid	CPR5-250	250	113.4	5"	127	1 1/4"	32	3.0	1.4
swivel	CPS6-500	500	226.8	6"	152	2"	51	9.0	4.1
brake	CPB6-500	500	226.8	6"	152	2"	51	9.0	4.1
rigid	CPR6-500	500	226.8	6"	152	2"	51	9.0	4.1



polyurethane plate  
caster with brake

### Casters with Polyurethane Tread

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPS5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
brake	CPB5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
rigid	CPR5P-300	300	136.1	5"	127	1 1/4"	32	3.0	1.4
swivel	CPS5P-500	500	226.8	5"	127	2"	51	8.0	3.6
brake	CPB5P-500	500	226.8	5"	127	2"	51	8.0	3.6
rigid	CPR5P-500	500	226.8	5"	127	2"	51	8.0	3.6
swivel	CPS6P-600	600	272.1	6"	152	2"	51	9.0	4.1
brake	CPB6P-600	600	272.1	6"	152	2"	51	9.0	4.1
rigid	CPR6P-600	600	272.1	6"	152	2"	51	9.0	4.1
swivel	CPS8P-700	700	317.5	8"	203	2"	51	10.5	4.8
brake	CPB8P-700	700	317.5	8"	203	2"	51	10.5	4.8
rigid	CPR8P-700	700	317.5	8"	203	2"	51	10.5	4.8

### EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA  
 Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065  
 www.eaglegrp.com  
 www.eaglehmc.com

### Certifications / Approvals



AutoQuotes



For custom configuration or fabrication needs, contact our SpecFAB® Division.  
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

EG01.05B Rev. 03/24

Spec sheets available for viewing, printing or downloading from our online literature library at our websites



Profit from the Eagle Advantage®

Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_

## Plate Casters



swivel/lock plate caster

### Swivel/Lock Casters

Polyurethane tread.

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel/lock	<b>CPL6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
swivel	<b>CPS6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
rigid	<b>CPR6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
brake	<b>CPB6Z-800</b>	800	362.9	6"	152	2"	51	9.0	4.1
swivel/lock	<b>CPL8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8
swivel	<b>CPS8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8
rigid	<b>CPR8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8
brake	<b>CPB8Z-900</b>	900	408.2	8"	203	2"	51	10.0	4.8



polymer  
plate caster

### Polymer Casters

Polyurethane tread.

type	model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>PCPS5-250</b>	250	90.7	5"	127	1 1/4"	32	2.8	1.3
lock	<b>PCPL5-250</b>	250	90.7	5"	127	1 1/4"	32	2.8	1.3



stainless steel  
pressure-washable  
caster (with brake)

### Stainless Steel Pressure-Washable Casters

Polyurethane tread.

type	model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CPS5S-300</b>	300	136.1	5"	127	1 1/4"	32	3.0	1.4
brake	<b>CPB5S-300</b>	300	136.1	5"	127	1 1/4"	32	3.0	1.4

#### EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglegrp.com

Printed in U.S.A.  
 ©2024 by Eagle Group

Rev. 03/24

Spec sheets available for viewing, printing or downloading from our online literature library at our websites

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.