



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Standard duty overall dimension of 24" wide x 60" x 69" tall. Four chrome plated wire shelves with one solid stainless base shelf. 5" resilient casters, two with brakes.

Heavy duty overall dimension of 29¾" wide x 64⅞" long x 72" tall. Chrome-plated dolly base with one solid stainless shelf and four 24" x 60" wire shelves. 6" polyurethane plate casters, two with brake. Enclosure panels on three sides.



heavy duty linen cart

Options / Accessories

- Cart Cover
- Tote boxes
- Shelf tray
- Tray slides
- Undershelf slides

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA
 Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065
www.eaglegrp.com
www.eaglemhc.com

For custom configuration or fabrication needs, contact our **SpecFAB® Division**.
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Linen Carts

MODELS:

- LC2460C
- LCD2460C

Design and Construction Features—both models

- Carts can be altered to meet changing requirements by adding or removing accessories. Any number of combinations can be made to customize any linen cart for a specific use.
- Numerically calibrated grooved posts, tapered split sleeves and shelf collars combine to make shelving assembly a simple two-step exercise: 1) Snap the split sleeves onto the posts at the desired location, and 2) slide the shelf collars over the split sleeves. A positive lock between the shelf and the split sleeves is created without the use of any tools, becoming stronger as weight is added to the shelving.
- Open-wire construction promotes higher visibility by allowing light to pass through the shelves, permits greater air circulation which helps reduce dust and contamination build-up, and increases the effectiveness of fire-suppression systems.
- Posts are numbered on vertical 1" (25mm) increments to ensure fast and level assembly; shelving can be adjusted up and down every inch for optimum cart configuration.
- All components are chrome-plated.

Standard model

- Four chrome-plated wire shelves.
- One solid stainless steel shelf.
- Chrome-plated 63" (1600mm) posts.
- 5" (127mm) resilient stem casters, two with brake.
- Donut bumpers.

Heavy Duty model

- Four chrome-plated wire shelves.
- One solid stainless steel shelf.
- Chrome-plated dolly frame with wraparound bumper.
- 6" (152mm) polyurethane casters, two with brake.
- Side and back enclosure panels.
- Chrome-plated posts.
- Aluminum split sleeves.

Certifications / Approvals





Profit from the Eagle Advantage®

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Linen Carts



standard linen cart



heavy duty linen cart

Standard Unit

model #	shelf width		shelf length		overall height		weight	
	in.	mm	in.	mm	in.	mm	lbs.	kg
LC2460C	24"	610	60"	1524	69"	1753	190	86.2

Heavy Duty Unit

model #	shelf width		shelf length		dolly width		dolly length		overall height		weight	
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
LCD2460C	24"	610	60"	1524	29 $\frac{3}{4}$ "	756	64 $\frac{7}{8}$ "	1648	72"	1829	240	108.9

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglemhc.com

Printed in U.S.A.
 ©2023 by Eagle Group

Rev. 10/23

Spec sheets available for viewing, printing or downloading from our online literature library at our websites

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.